

电容式接近开关(DC 3线式,4线式)

M18, M30

M18x60		M30x60				M30x60					
5.0mm		8.0mm		10mm		15mm					
埋入		非埋		埋入		非埋					
CM18-M05NA-Y3U4/P60	1	CM18-F08NA-Y3U4/P60	CM30-M10NA-Y3L2/C60	1	CM30-F15NA-Y3L2/C60	CM30-M10NA-Y3U4/C60	1	CM30-F15NA-Y3U4/C60			
CM18-M05NB-Y3U4/P60	2	CM18-F08NB-Y3U4/P60	CM30-M10NB-Y3L2/C60	2	CM30-F15NB-Y3L2/C60	CM30-M10NB-Y3U4/C60	2	CM30-F15NB-Y3U4/C60			
CM18-M05NC-Y3U4/P60	3	CM18-F08NC-Y3U4/P60	CM30-M10NC-Y3L2/C60	3	CM30-F15NC-Y3L2/C60	CM30-M10NC-Y3U4/C60	3	CM30-F15NC-Y3U4/C60			
CM18-M05PA-Y3U4/P60	4	CM18-F08PA-Y3U4/P60	CM30-M10PA-Y3L2/C60	4	CM30-F15PA-Y3L2/C60	CM30-M10PA-Y3U4/C60	4	CM30-F15PA-Y3U4/C60			
CM18-M05PB-Y3U4/P65	5	CM18-F08PB-Y3U4/P60	CM30-M10PB-Y3L2/C60	5	CM30-F15PB-Y3L2/C60	CM30-M10PB-Y3U4/C60	5	CM30-F15PB-Y3U4/C60			
CM18-M05PC-Y3U4/P60	6	CM18-F08PC-Y3U4/P60	CM30-M10PC-Y3L2/C60	6	CM30-F15PC-Y3L2/C60	CM30-M10PC-Y3U4/C60	6	CM30-F15PC-Y3U4/C60			
CM18-M05SZ-Y3U4/P60	9	CM18-F08SZ-Y3U4/P60	CM30-M10SZ-Y3L2/C60	9	CM30-F15SZ-Y3L2/C60	CM30-M10SZ-Y3U4/C60	9	CM30-F15SZ-Y3U4/C60			
CM18-M05ZZ-Y3U4/P60	22	CM18-F08ZZ-Y3U4/P60	CM30-M10ZZ-Y3L2/C60	22	CM30-F15ZZ-Y3L2/C60	CM30-M10ZZ-Y3U4/C60	22	CM30-F15ZZ-Y3U4/C60			
5mm(1mm~8mm)	8mm(1mm~10mm)	10mm(2mm~15mm)	15mm(3mm~20mm)	10mm(2mm~15mm)	15mm(3mm~20mm)	10mm(2mm~15mm)	15mm(3mm~20mm)				
3-15%	3-15%	3-15%	3-15%	3~15%	3~15%	3~15%	3~15%				
铁18x18x1mm	铁24x24x1mm	铁30x30x1mm	铁45x45x1mm	铁30x30x1mm	铁45x45x1mm	铁30x30x1mm	铁45x45x1mm				
100Hz	80Hz	70Hz	60Hz	70Hz	60Hz	70Hz	60Hz				
≤Sn±3%		≤Sn±3%		≤Sn±3%		≤Sn±3%					
≤0.01mA		≤0.01mA		≤0.01mA		≤0.01mA					
≤15mA		≤15mA		≤15mA		≤15mA					
≤200mA		≤200mA		≤200mA		≤200mA					
≤2V		≤2V		≤2V		≤2V					
极性反接保护;上电脉冲抑制保护;负载短路保护		极性反接保护;上电脉冲抑制保护;负载短路保护		极性反接保护;上电脉冲抑制保护;负载短路保护		极性反接保护;上电脉冲抑制保护;负载短路保护					
动作指示灯(黄色)		动作指示灯(黄色)		动作指示灯(黄色)		动作指示灯(黄色)					
-25~+70°C		-25~+70°C		-25~+70°C		-25~+70°C					
≤Sn±10%		≤Sn±10%		≤Sn±10%		≤Sn±10%					
-25~+80°C		-25~+80°C		-25~+80°C		-25~+80°C					
50MΩ以上(DC 500V兆欧表),充电部整数和外壳之间		50MΩ以上(DC 500V兆欧表),充电部整数和外壳之间		50MΩ以上(DC 500V兆欧表),充电部整数和外壳之间		50MΩ以上(DC 500V兆欧表),充电部整数和外壳之间					
符合标准EN60947-5-2		符合标准EN60947-5-2		符合标准EN60947-5-2		符合标准EN60947-5-2					
IP67		IP67		IP67		IP67					
4针M12连接器		电缆线2M; 外径 φ 5.0mm		4针M12连接器		4针M12连接器					
外壳材料:塑料;检测面材料:塑料		外壳材料:黄铜镀镍;检测面材料:塑料		外壳材料:黄铜镀镍;检测面材料:塑料		外壳材料:黄铜镀镍;检测面材料:塑料					
注: 1,2,3,4,5,6,9,22为接线图号, 请见05页。											

1 电感式传感器

2 电容式传感器

3 磁感式传感器

4 光电传感器

5 传感器附件

6 词汇表